

# cPS-H640/AC, H640/48

400 W 6U CompactPCI® Hot-Swappable Redundant Power Supply



## Features

- PICMG® 2.11 CompactPCI® Power Interface compliant
- 6U CompactPCI® 8HP form factor
- PICMG® 2.11 47-pin CompactPCI® in-rack power module interface
- 400 W DC output, maximum 480 W peak output
- Active PFC (Power Factor Correction) meets IEC1000-3-2 Harmonic Correction
- Internal OR-ing Diodes for N+1 redundancy
- Hot swappable
- Active current sharing
- EMI meet EN 55022 & FCC Class A
- Supports remote ON/OFF
- Supports power failure signal & degradation signal

## Specifications

| Model Name                                 | cPS-H640/AC   | cPS-H640/48   |
|--|---|---------------|
| PICMG Standards                            | PICMG® 2.11 CompactPCI 47-pin Power Interface compliant   |               |
| Form Factor                                | 6U cPCI (233.33 x 160 mm), 2-slot (8HP) wide  |               |
| Input Voltage                              | 100-240 10% V AC  | 36-72 V DC    |
| Input Frequency                            | 50-60 5% Hz   | DC            |
| Input Current                              | 5.1 A @115 V AC / 2.5 A @ 230 V AC  | 12A @ 48 V DC |
| Inrush Current                             | < 30 A @230 V AC  | N/A           |
| Power Factor Correction (PFC, only for AC) | Typical 0.97-0.99<br>Meets Harmonic Correction IEC1000-3-2  |               |
| Output Voltage/Current                     | 5 V: Typ. 40.0 A, Max. 50.0 A<br>3.3 V: Typ. 20.0 A, Max. 40.0 A<br>+12 V: Typ. 10.0 A, Max. 15.0 A<br>-12 V: Typ. 2.0 A, Max 5.0 A<br><br>** Max. load is the continuous operating load of each rail individually. The Max. load of each rail cannot be drawn from all outputs simultaneously. |               |
| Output Voltage Minimum Load                | 1.0 A @ +5 V  |               |
| Output Wattage                             | Typical 400 W continuous, maximum 480 W peak output   |               |
| Line Regulation                            | Typical 0.1%  |               |
| Load Regulation                            | Typical 1-3%  |               |
| Ripple                                     | 50 mV @ +5 V and 3.3 V outputs, 120 mV @ +12V and -12V outputs  |               |
| Hold-up Time                               | 10 ms after power fail signal   |               |
| Efficiency                                 | Typical 79-83%  |               |
| Output voltage sense and current sharing   | Available at 5 V , 3.3 V and +12 V outputs  |               |
| N+1 Redundancy                             | Installed with internal OR-ing diodes at all outputs for N+1 redundancy operation   |               |
| Remote ON/OFF                              | Available at [INH#] & [EN#]   |               |

|                          |   |     |
|--------------------------|---|-----|
| Power Failure Signal     | Available at [FAL#] pin   |     |
| Power Degradation Signal | Available at [DEG#] pin   |     |
| Protections              | Over Temperature Protection (OTP): 70°C<br>Over Current Protection (OCP): Installed at each rail<br>Over Load Protection (OLP): Typical 120% max. load, fully protected against output overload or short circuit.<br>Over Voltage Protection (OVP): Built-in at all outputs |     |
| Status LED               | < Green LED > [POWER] means valid input voltage<br>< Amber LED > [FAULT] means a critical fault   |     |
| Earth Leakage            | < 0.9mA @ 230 V AC >  | N/A |
| Operating Temp.          | 0° to 70°C (0° to +40°C at full load with specified air flow. De-rates linearly to 50% at +70°C.)   |     |
| Storage Temp.            | -20°C to +85°C  |     |
| Humidity                 | 20% to 90% non-condensed  |     |
| Shock                    | 15 G peak-to-peak, 11 ms duration, non-operation  |     |
| Vibration                | Operation: 1.88 Grms, 5-500 Hz, each axis   |     |
| Cooling Requirement      | Minimum 20 CFM airflow is required for typical full rating power  |     |
| Compliance               | IEC950, EN 55022, FCC Class A, IEC60950 Class I   |     |

## Ordering Information

| Model Number | Description/Configuration   |
|--------------|---|
| cPS-H640/AC  | PICMG® 2.11 47-Pin Hot-Swap Redundant 6U Compact-PCI 8HP 400 W Power Module with Universal AC Input |
| cPS-H640/48  | PICMG® 2.11 47-Pin Hot-Swap Redundant 6U Compact-PCI 8HP 400 W Power Module with 36-72 V DC Input   |